

75W21K-U 75" Interactive Touchscreen Monitor



The latest W-series touchscreen now offers an inbuilt Android operating system with up to full 20 touch control. The OPS slot is standard on all models making the integration of attaching the optional slim line PC an easy installation.

Key Features

- ▶ 4K resolution
- ▶ Up to IR 20 touch[^]
- ▶ HDMI/PC inputs
- ▶ Built-in speakers
- ▶ USB media player and PVR
- ▶ Android Operating System 8.0
- ▶ EShare Pro Wireless Presentation System
- ▶ 5 Year Warranty



[^]Windows only. 10 touch for Android. Single touch on Mac OSX.

Specifications

Type	75" Interactive Touchscreen Monitor	
Screen size	75 inches (16:9)	
Model	A2T-75W21K-U	
Display	Panel	LED panel
	Screen Size	1650 x 928mm
	Resolution	3840 x 2160
	Colours	1.07 billion colours
	Brightness	450 cd/m ²
	Contrast	1200:1
	Viewing Angle	>178°

Specifications (continued)

Inputs	Built-in Speakers	8Ω x 15W x 2
	Audio Stereo	Stereo
		1 x DP (Display Port)
		1 x VGA
		Component
		4 x USB Port (Media formats for playback and recording: JPG, BMP, PNG images... AVI, MPG, DAT, VOB, DIV, MOV, MKV, RM, RMVB, MP4, MPEG, TS, TRP, WMV, ASF and FLV video... plus WMA, MP3, M4A audio)
		3 x HDMI port
	LAN	2 x LAN
	Serial Port Input	1x RS232
	Touch Input	2 x USB - B type
Outputs	Audio Input	1 x PC audio in
		1 x 3.5mm mic input
		1 x AV Out
		1 x HDMI Out
		1 x S/PDIF Out
Touch Screen		1 x Audio Out
	Surface Protection	4mm Toughened Glass
	Induction Method	Infrared with 20 touch
	Writing Style	(Finger, stylus)
	Response Time	10ms
	Touch Accuracy	±1.0mm
	Mac Driver Support	OSX 10.1 - 10.15.1
Other Features	Windows 10/8/7 & Android	Multi Touch
	Windows XP, Linus, Mac OS X, Chrome	Single Touch
		Supports auto turn off, sleep timer and more Resume function after device shut-down
Housing Material		Commercial grade aluminium/metal plate
Input Voltage		AC: 100 ~ 240v 60/50hz
Power Rate		400W
Standby		≤0.5W
In The Box		Manual, Remote Control, 3m Power Cord, 3m USB Cable, Stylus, 3m HDMI Cable, Warranty Card, Wall Mount
Product Weight		58kg
Packaged Weight		75kg
Environmental Factors		Operating Temperature: 0°C - 40°C
		Operation humidity: 20% - 80%
		Storage Temperature: -10°C - 60°C
		Storage Humidity: 10% - 80%
Dimensions	Dimensions (W x H x D)	1736× 1035 × 104mm
	Package Size (W x H x D)	1880 × 1160 × 280mm
	VESA Mount	600 x 400mm

For more information contact: info@azt.io